

## UNIVERSAL FILMS FOR “SLAVAFLEX” FLEXIBLE PACKAGING

### Lamination films

#### Structures:

- PE — frozen product;
- PE — bulk products;
- PE — fat containing food;
- PE — alcohol-based products;
- PA/PE — seafood, fish;
- PA/PE — household chemical goods;
- PE/PA/PE, PE/EVOH/PE, PE/PA/EVOH/PA/PE and the other combinations — long shelf life products;
- And other combinations of these materials.



**Range of products:** from 30 microns to 130 microns thick, up to 2200 mm wide.

### FILMS FOR PACKING FOOD PRODUCTS ON FLOWPACK, DOYPACK, SACHET LINES

They are designed for packing sausages, fish, seafood, mayonnaise, sauces, condensed milk, dumplings, snack products, grocery and confectionary products, spices and so on.

#### Structures:

- PET//PE;
- BOPP//PE;
- PET//PET met//PE/EVOH/PE;
- BOPP//BOPP met;
- OPA//PE;
- PA/PE;
- PET//PE/EVOH/PE;
- PET//PE/PA/EVOH/PA/PE;
- BOPP//PETmet //PE/EVOH/PE;
- And other combinations of these materials.



**Range:** from 45 microns to 175 microns thick. Up to 2200 mm wide. The production of white film and application of surface and interlayer print up to 8 colors is possible.

### FILMS FOR PACKING NON-FOOD PRODUCTS ON FLOWPACK, DOYPACK, SACHET LINES

Application: packing household chemicals, wet wipes, soils, fertilizers, etc.

#### Structures:

- PE//PE;
- PET//PE;
- BOPP//PE;
- PET//BOPPmet//PE;
- And other combinations of these materials.

**Range:** Range of products: from 45 microns to 150 microns thick. The production of white film and application of surface and interlayer print up to 8 colors is possible.



## UPPER “SLAVAFLEX” COATING FILMS FOR THERMOFORMING EQUIPMENT AND TRAY SEALERS (SEALING FINISHED TRAYS)

Application: packing the following products in vacuum or modified gas atmosphere: cooled and frozen meat, meat products, cooled and frozen poultry, sausages and delicatessen products, cooled and frozen fish, cooled and frozen seafood, semi-finished products, cheeses and bakery products. The films can be used for all types of thermo forming machines: Multivac, Tiromat, Webomatic, Henkovac, Hajek, Tiropac, ULMA, GEA, etc.

### SLAVAFLEX films structures, medium barrier:

- PET//CPP;
- PET//PE;
- PA/PE;
- OPA//PE;
- PET//OPA//PE.

### SLAVAFLEX films structures, high barrier:

- PET//PE/EVOH/PE;
- PET//PE/PA/EVOH/PA/PE;
- PET//PE/EVOH/PP;
- PET//PA/PA/EVOH/PA/PE.

**Range of products:** from 45 microns to 175 microns thick.

Up to 1500 mm wide. Upon the request of the customer, possible is production of white film, printing on surface of the film or interlayer print up to 8 colors is possible as well.

The options include production of films with such additional properties as: easy peeling (PEEL effect), anti-fog effect (AF effect) and reclose effect.

Various formulations designed for adhesion with various materials (polyethylene PE, polypropylene PP, etc.) are available.

